
North America's Leader in Hazardous Material Information Management
1905 Aston Avenue, Carlsbad, CA 92008
Phone (800) 451-8346 Fax (760) 602-8888

MSDS PRODUCT INFORMATION

Date: 10/07/2005
To: MSDS Requester
From: 3E Company
Subject: The MSDS you have requested

MSDS NOT REQUIRED

In response to your request for a Material Safety Data Sheet, according to the OSHA Hazard Communication Standard (Right-to-Know), the following item is an article. Articles are defined in 29 CFR 1910.1200(c). Products such as Drugs, cosmetics, food, or alcoholic beverages, wood or wood products, and tobacco or tobacco products, as defined in 29 CFR 1910.1200(b)(6), are exempt from the Hazard Communication Standard. Items that are considered articles, as defined in 29 CFR 1910.1200(c), are also exempt from this Standard. Therefore, the manufacturer is not required to provide an MSDS for this product.

MSDS DISCONTINUED PRODUCT

In response to your request for a Material Safety Data Sheet, the manufacturer has discontinued the product listed below. The MSDS Attached is the most current version, or an MSDS is no longer available.

MSDS BEST COPY AVAILABLE

The MSDS attached is the best copy available from the manufacturer.

MANUFACTURER NO LONGER IN BUSINESS

In response to your request for a Material Safety Data Sheet, a current MSDS could not be obtained for this product. It has been determined that the manufacturer listed below is no longer in business. A current address and phone number could not be located.

Manufacturer: Smiland Paint Company

Product Name: Conco Pro Paints (900, 901, 904, 910, 920, 940, 979)(DISCONTINUED)



3E COMPANY *North America's Leader in Hazardous Material Information Management*

1905 Aston Avenue, Carlsbad, CA 92008

Phone (800) 451-8346 Fax (760) 602-8856

MSDS DISCONTINUED PRODUCT

Date: 09/24/2001

To: MSDS Requester

From: 3E Company

Subject: The MSDS you have requested

In response to your request for a Material Safety Data Sheet, the manufacturer has discontinued the product listed below. The MSDS attached is the most current version, or an MSDS is no longer available.

Manufacturer: Smiland Paint Company

ProductName: Conco Pro Paints (900, 901, 904, 910, 920, 940, 979)(DISCONTINUE

Material Safety Data Sheet

Page:

H F R P
HMIS Codes: 2* 2 0 B

Brand Name: Conco• Pro
Product Number: 900
Product Description: Int.-Ext. High Performance Oil Base S-G Enamel

Section I - Manufacturer Identification

Manufacturer's Name: Conco Paint Company
Address: 12234 Los Nietos Rd., Santa Fe Springs, CA 90670
Emergency Phone: (800) 486-7889 Information: (800) 486-7889
Date Revised: 10/02/98

SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE mm Hg @ TEMP	WEIGHT PERCENT
NAPHTHA (PETROLEUM), HEAVY ALKYLATE ACGIH TLV/TWA: 300 PPM	64741-65-7	2.6 68 F	9.2
NAPHTHA (PETROLEUM), MEDIUM ALIPHATIC OSHA PEL/TWA: 100 PPM; ACGIH TLV/TWA: 100 PPM	64742-88-7	0.5 68 F	8.2
NAPHTHA (PETROLEUM), HYDROTREATED HEAVY OSHA PEL/TWA: 400 PPM; ACGIH TLV/TWA: 400 PPM	64742-48-9	10 68 F	5.4
NAPHTHA (PETROLEUM), LIGHT AROMATIC ACGIH/TWA: 100 PPM; FEDERAL PEL: 100 PPM	64742-95-6	< 5 100 F	1.8
4-TRIMETHYLBENZENE (PSEUDOCUMENE) OSHA PEL: 25PPM; ACGIH -TLV/TWA: 25 PPM; ACGIH -TLV/STEL: 35 PPM	95-63-6	16 100 F	1.1
NAPHTHA (PETROLEUM), HYDROTREATED LIGHT ACGIH TLV/TWA: 300 PPM	64742-47-8	10 68 F	1.0

* Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING RANGE: 235 F - 355 F
VAPOR DENSITY: Heavier than air.
COATING V.O.C.: 364 g/l
SOLUBILITY IN WATER: None.
APPEARANCE AND ODOR: Typical for solvent based paints.

SPECIFIC GRAVITY (H₂O=1): 1.27
EVAPORATION RATE: Slower than ether.
MATERIAL V.O.C.: 364 g/l

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: 113 F
FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 0.7
METHOD USED: TCC
UPPER: 7.0

EXTINGUISHING MEDIA: Foam, CO₂, or Dry Chemical.

SPECIAL FIREFIGHTING PROCEDURES

Use self-contained breathing apparatus with full facepiece operated in pressure demand or other positive pressure mode. During emergency conditions, overexposure to decomposition products may cause health hazard.

USUAL FIRE AND EXPLOSION HAZARDS

vapors are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights, or other flames and ignition sources at locations distant from material handling points. Keep containers tightly closed. Isolate from heat sparks, electrical equipment, and open flames. Closed containers may explode on exposure to high temperatures.

===== SECTION V - REACTIVITY DATA =====

STABILITY: Stable.

CONDITIONS TO AVOID

Do not expose to high temperatures or open ignition sources.

INCOMPATIBILITY (MATERIALS TO AVOID)

Avoid contact with strong oxidizing agents.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS

May form toxic materials; Carbon Dioxide, Carbon Monoxide, Various Hydrocarbons, etc. on thermal decomposition.

HAZARDOUS POLYMERIZATION: Will not occur.

===== SECTION VI - HEALTH HAZARD DATA =====

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

May cause nasal and respiratory irritation, dizziness, weakness, fatigue, nausea, headache, possible unconsciousness and even asphyxiation.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

EYES: May cause severe irritation, redness, tearing, and blurred vision. **SKIN:** Redness or dryness.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Moderate irritation, redness, and defatting dermatitis.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Can cause gastrointestinal irritation, nausea, vomiting, and diarrhea.

HEALTH HAZARDS (ACUTE AND CHRONIC)

ACUTE: Irritation of skin, eyes, and respiratory tract. Aspiration of material into lungs can cause chemical pneumonitis which can be fatal. **CHRONIC:** Prolonged or repeated exposure above TLV may result in permanent brain and nervous system damage. **CHRONIC:** Prolonged or repeated exposure to this product may cause cancer.

CARCINOGENICITY: NTP CARCINOGEN: No IARC MONOGRAPHS: No OSHA REGULATED: Yes

WARNING! This product contains chemical(s) known to the State of California to cause cancer. (California Health and Safety Code Section 25249.5) (Prop. 65). **WARNING!** This product contains chemical(s) known to the State of California to cause birth defects or other reproductive harm. (California Health and Safety Code Section 25249.5) (Prop. 65).

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

May be aggravating to some skin and respiratory conditions, and to pre-existing liver and/or kidney disorders.

EMERGENCY AND FIRST AID PROCEDURES

EYES: Flush with large amounts of water for at least 15 minutes. Take to a physician.

SKIN: Wash affected areas with soap and water. Remove contaminated clothing. If irritation persists, consult physician.

INHALATION: Remove to fresh air. Restore breathing. Treat symptomatically. Consult physician.

INGESTION: Drink 1 or 2 glasses of water to dilute. DO NOT INDUCE VOMITING. CONSULT A PHYSICIAN OR POISON CONTROL CENTER

IMMEDIATELY. TREAT SYMPTOMATICALLY.

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Eliminate all ignition sources. Dike, contain, or absorb with inert materials. Transfer to containers for recovery or disposal. Prevent runoff into sewers, streams, or other bodies of water.

W. E DISPOSAL METHOD

Dispose of in accordance with all local, state and federal regulations.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Do not store or use near sources of high temperatures, near fire or open flame, or other ignition sources.

OTHER PRECAUTIONS

DO NOT TAKE INTERNALLY. Avoid prolonged or repeated exposure to levels above TLV. KEEP OUT OF REACH OF CHILDREN.

===== SECTION VIII - CONTROL MEASURES =====

RESPIRATORY PROTECTION

If TLV is exceeded, use NIOSH/MSHA approved organic vapor, mist and dust, supplied air, or self-contained breathing apparatus. Avoid breathing sanding dust.

VENTILATION

Use adequate mechanical (general and/or local) ventilation to maintain exposure below TLV.

PROTECTIVE GLOVES

Wear resistant gloves such as Nitrile Rubber.

EYE PROTECTION

Use chemical splash goggles or OSHA permitted safety glasses.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

Wear impervious clothing. Eyewash station.

WORK/HYGIENIC PRACTICES

Wash hands before eating or using restrooms. Remove and wash all contaminated clothing before reuse.

===== SECTION IX - DISCLAIMER =====

The information contained herein is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determination of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees.